

# Lithium Iron Phosphate (LiFePO4) Battery

## LFP12.8-100(12.8V100Ah)

### Features of LiFePO4 Battery


- **Longer Cycle Life:** Offers up to 20 times longer cycle life and five times longer float/calendar life than lead acid battery, helping to minimize replacement cost and reduce total cost of ownership.
- **Lighter Weight:** About 40% of the weight of a comparable lead acid battery. A 'drop in' replacement for lead acid batteries.
- **Higher Power:** Delivers twice power of lead acid battery, even high discharge rate, while maintaining high energy capacity.
- **Wider Temperature Range:** -20°C~60°C.
- **Superior Safety:** Lithium Iron Phosphate chemistry eliminates the risk of explosion or combustion due to high impact, overcharging or short circuit situation.
- **Increased Flexibility:** Modular design enables deployment of up to four batteries in series and up to ten batteries in parallel.



### Application

- Electric vehicles, electric mobility
- Solar/wind energy storage system
- UPS, backup power
- Telecommunication
- Medical equipment
- Lighting

### Cycle Life Curve



### Specification

Electrical Characteristics	Nominal Voltage	12.8V
	Nominal Capacity	100Ah (C <sub>5</sub> ,25°C)
	Energy	1280Wh
	Internal Resistance	≤150mΩ
	Cycle Life	>3000 cycles @1C 100%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.2C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	14.6±0.2V
	Charge Mode	0.2C to 14.6V, then 14.6,charge current 0.02C(CC/CV)
	Charger Current	50A
	Max. Charge Current	100A
	Charge Cut-off Voltage	14.8V±0.2V
Standard Discharge	Continuous Current	100A
	Max. Pulse Current	300A(<3s)
	Discharge Cut-off Voltage	10V
Environmental	Charge Temperature	0 °C to 45 °C (32F to 113F) @60%25% Relative Humidity
	Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60%25% Relative Humidity
	Storage Temperature	0 °C to 40 °C (32F to 104F) @60%25% Relative Humidity
	Water Dust Resistance	
Mechanical	Cell & Method	3.2V50AH-4S2P
	Plastic Case	ABS
	Dimensions (in./mm.)	330*173*220 mm
	Weight (lbs./kg.)	10.3Kg
	Terminal	M8
	Protocol (optional)	NO
	BMS	4S100A