

VCT

450/750 V, 70°C FLEXIBLE CONDUCTOR
PVC INSULATED AND SHEATHED, 4 CORES



APPLICATION

- Use for general purpose
- Use for connecting electric appliance
- Laid on cable trays
- install in duct in ground or direct burial in ground

TESTING VOLTAGE : 2,500 Volts

REFERENCE STANDARD :

TIS 11-2553 PART 101, TABLE 7

CABLE STRUCTURE

CONDUCTOR : Flexible Annealed Copper

CLASS 5 Size 4 - 35 mm²

INSULATION : Polyvinyl chloride type PVC/D

SHEATHED : Polyvinyl chloride type PVC/ST5

CLASSIFICATION

Maximum Conductor Temperature : 70°C

Circuit Voltage does not exceed

450/750 Volts (U₀/U)

450 Volts between Line to Earth (U₀)

750 Volts between Line to Line (U)

Technical Data



TIS 11-2553 PART 101, TABLE 7

Nominal cross sectional area	Conductor type	Maximum Diameter of wires	Diameter (approx.)	Nominal insulation thickness	Nominal sheathed thickness	Maximum Overall diameter	Maximum conductor resistance at 20°C	Minimum insulation resistance at 70°C	Current rating in free air	Cable weight (approx.)	Standard packing
mm ²	Class	mm	mm	mm	mm	mm	Ω/km	MΩ-km	A	kg/km	m
4	5	0.31	2.59	0.9	1.8	17.0	4.95	0.0084	26	350	100/C
6	5	0.31	3.59	0.9	2.0	19.5	3.30	0.0071	34	490	100/C
10	5	0.41	4.67	1.1	2.2	24.0	1.91	0.0068	47	800	500/D
16	5	0.41	5.86	1.1	2.6	28.0	1.21	0.0050	63	1,100	500/D
25	5	0.41	7.31	1.3	2.8	33.0	0.780	0.0048	83	1,700	500/D
35	5	0.41	8.67	1.3	3.1	37.0	0.554	0.0041	102	2,200	500/D

Conductor Class 5 : Flexible

C : Packing in coil

D : Packing in drum

Core Color : Blue, Brown, Black, Grey

การใช้งาน

- ใช้งานทั่วไป
- ใช้ต่อเข้ากับเครื่องใช้ไฟฟ้า
- วางบนรางเคเบิล
- รอยต่อฝังดินหรือฝังดินโดยตรง