




SC20 - SC518 : BRACKET & ARM

Features:


- For installation of Street lighting
- Strong and durable steel structure
- Easy installation
- Finishing choice
 - Powder Coated Grey
 - Hot-dipped galvanizing
- ASTM A123-89a Galvanizing Standard

SC20



| Model | Type | Finishing | Diameter D (mm) | Jut L (mm) | H1 (mm) | H2 (mm) |
|-------------|----------------|-----------------------|-----------------|------------|---------|---------|
| SC20B10/150 | 1" x 1.50m | Silver Metallic | 33mm (1") | 1100 | 150 | 740 |
| SC20B15/150 | 1 1/2" x 1.50m | Silver Metallic | 48mm (1 1/2") | 1100 | 150 | 740 |
| SC20G10/150 | 1" x 1.50m | Hot-dipped Galvanized | 33mm (1") | 1100 | 150 | 740 |
| SC20G10/200 | 1" x 2.00m | Hot-dipped Galvanized | 33mm (1") | 1530 | 150 | 990 |
| SC20G15/150 | 1 1/2" x 1.50m | Hot-dipped Galvanized | 48mm (1 1/2") | 1100 | 150 | 740 |
| SC20G15/200 | 1 1/2" x 2.00m | Hot-dipped Galvanized | 48mm (1 1/2") | 1530 | 150 | 990 |
| SC20G15/250 | 1 1/2" x 2.50m | Hot-dipped Galvanized | 48mm (1 1/2") | 1950 | 150 | 1240 |
| SC20G15/300 | 1 1/2" x 3.00m | Hot-dipped Galvanized | 48mm (1 1/2") | 2420 | 150 | 1500 |

SC518



| Model | Ref. | Type | Finishing | Diameter D(mm) | Jut L (mm) |
|-----------|------|----------------|-----------------------|----------------|------------|
| SC518M165 | B1 | 1 1/2" x 1.20m | Hot-dipped Galvanized | 48mm (1 1/2") | 1200 |
| SC518M220 | B2 | 1 1/2" x 1.80m | Hot-dipped Galvanized | 48mm (1 1/2") | 1800 |
| SC518M300 | B3 | 1 1/2" x 2.50m | Hot-dipped Galvanized | 48mm (1 1/2") | 2500 |
| SC518L165 | A1 | 2" x 1.20m | Hot-dipped Galvanized | 60mm (2") | 1200 |
| SC518L220 | A2 | 2" x 1.80m | Hot-dipped Galvanized | 60mm (2") | 1800 |
| SC518L300 | A3 | 2" x 2.50m | Hot-dipped Galvanized | 60mm (2") | 2500 |